THERMISTOR THERMOMETER





Safe, Quick and Easy to read the boiler temperature in faraway place!!



EXTERNAL PROBE P/N: VZ889PNL Length: 500mm

Diameter: 5mm Handle length: 65mm Cable length: 1500mm



IP65: protected against jets of water

IP66: protected against strong jets of water

IP67 : protected against immersion in water up to 1 meter for 30 minutes

IP68: protected against immersion in water under pressure for long periods

Ordering Code

VZ8891AZ, 8891 long probe thermometer VZ889PNL, 8891 long probe VM4889PD, stainless probe holder

*Available for EB project

IP67 Waterproof Thermometer with Long Probe 8891

- ■The most cost effective waterproof temperature monitor with super large LCD and long probe
- ■0.1 degree resolution and high accuracy
- ■IP67 waterproof meter and external probe
- ■Wall mounted design for long time using
- ■4 alkaline AAA batteries provides 1 year battery life
- ■Stainless long & durable external probe
 - -length:0.5m
 - -diameter:5mm
 - -handle length(nylon+glass fiber)
 - -cable length(silicon):1.5m









Imperial Battery	
Model	8891
Temp. Range (thermistor)	-10~110°C(-14~230°F)
Temp. Resolution	0.1°C(0.1°F)
Temp. Accuracy	+/-1 ^o C(+/-1.6°F)
Temp. Response time	2 minutes typical
LCD update time	10 seconds
LCD size (mm, HxW)	45x96
Operating temp.	0~50°C
Operating RH%	Humidity < 80%
Storage temp.	-20~50°C
Storage RH%	Humidity < 90%
Meter Dimension(mm,LxWxT)	122x85x30
Meter Weight	~200g
Probe size(mm) Length Diameter Handle length(mm) Cable length(mm)	500 5 65 1500
Probe Weight	~80g

AAA ALKALINEx 4pcs Battery Standard Package Meter, probe, probe holder, battery, manual, plain box **Optional Accessory** External probe



STAINLESS PROBE HOLDER P/N:P/N:VM4889PD Included in standard package to offer you steady probe support!



