

UT330 Series USB Datalogger

NEW




UT330T



UT330TH



UT330THC



UT330T/UT330TH




UT330THC



°C/°F selection



1m drop proof



USB interface



LED alarm



Low battery indication



Auto power off

UT330 series dataloggers use high-precision temperature and humidity sensors for long period monitoring and recording. They are widely used in food processing, cold chain and other fields.

Specifications	Range	UT330T	UT330TH	UT330THC
Temperature	-30.0°C~70°C	√	√	√
Accuracy	-20°C~40°C <-20°C or >40°C	±0.4°C ±0.8°C	±0.4°C ±0.4°C	±0.4°C ±0.4°C
Resolution	-0.1°C/0.1°F	√	√	√
Temperature offset settings		√	√	√
Humidity	0%RH~100%RH		±2.5%RH	±2.5%RH
Resolution	0.1%RH		√	√
Humidity offset settings			√	√
MAX/MIN/MKT		√	√	√
PC software		√	√	√
Data storage		64000	64000	64000
PC software		√	√	√
Mobile APP				√
IP rating		IP65		

Characteristics

Power	CR2032
Display	23 x 20mm
Product net weight	UT330T: 56g, UT330TH: 57.4g, UT330THC: 56.4g
Product size	UT330T: 38 x 96 x 14mm, UT330TH/UT330THC: 38 x 105 x 14mm
Standard accessories	Batteries, bracket, screws, stickers, English manual
Standard individual packing	Gift box

