

Bench-type Digital Multimeter

- XDM2041



- + 4 inch (480x320) high resolution LCD
- + 55,000 counts
- + Up to 65 readings per second
- + True RMS AC voltage / current measurement
- + Dual line display supported
- + Trend analysis accessible in chart mode
- + SCPI supported

	Measurement Range	Optimal Accuracy
DC Voltage	50.000mV - 1000.0V	0.025% + 5
True RMS AC Voltage	500mv - 750v	0.5% + 30
AC Voltage	500uA / 5000uA / 50mA / 500mA	0.15%+20
	5A / 10A	0.5%+10
True RMS AC Current	500uA-500mA	0.5%+20
	5A-10A	1.5%+20
Resistance	500Ω	0.1%+10
	5KΩ / 50KΩ / 500KΩ	0.1%+5
	5MΩ	0.25%+5
	50MΩ	0.1%+10
Four-wire resistance	500Ω	0.1%+10
	5KΩ / 50KΩ	0.1%+5
Diode	3.0000 V	
Continuity	1000 Ω	
Frequency	10.000Hz-60MHz	±(0.2%+8)
Capacitance	50nF-500uF	2.5%+5
	5mF-50mF	5%+8
Temperature	K-type, PT100	
Display	55,000	
Logging Duration	15ms - 9999.999s	
Logging Length	1,000pts	
General		
Communication Interface	Rs232	
Dimensions (W×H×D)	235 x 110 x 295 (mm)	
Device Weight	3.00kg	

Specifications subject to change without prior notice.

+ Accessories The accessories subject to final delivery.



Power Cord



Quick Guide



Fuse



Multimeter Lead



Alligator Clip